




EUROVAC AC / DC

Main Applications

- Hospital Crash Carts
- Patient Transfer
- Long Term Home Care
- Tracheostomy
- EMS / Ambulance
- Bed Side

TECHNICAL FEATURES

Model	EUROVAC AC / DC BATTERY OPERATED	EUROVAC ON TROLLEY
Housing	ABS Plastic Moulded	ABS Plastic Moulded on four castors with Foot Switch
Max. Vacuum / LPM	600 mm Hg, 55 LPM	575 mm Hg, 45 LPM
Pump Type	Diaphragm Pump	Diaphragm Pump
Jars	1 x 2 Ltr. PC Jar	2 x 2 Ltr. PC Jar
Filter	Bacterial Filter Autoclavable / Reusable	Bacterial Filter Autoclavable / Reusable
Tubing	8 mm ID x 2 mtr. (Silicon)	8 mm ID x 2 mtr. (Silicon)
Vacuum Gauge	6.25 cm dia 0-760 mm Hg	6.25 cm dia 0-760 mm Hg
Power Supply	220 V AC, 50 / 60 Hz, 70 Watt, 12 V DC Internal Rechargeable Battery (12 V 4.5 Amp)	220 V AC, 50 / 60 Hz 90 Watt
Battery	Lead Acid	N/A
Battery Backup / Operative Time	180 minutes (with fully charged / new battery)	N/A
Noise Level	55 dBA ± 3	55 dBA ± 3
Dimensions	43 x 22 x 37 cms	48 x 48 x 114 cms
Net Weight	10.5 Kg	8 Kg + 9 Kg Trolley
Overflow Safety	Mechanical & Electronic Sensor	Mechanical & Electronic Sensor
Accessories	Car Charger & Power Adaptor 	-
Optional	Ni-cd / Li-ion Battery	110 V
Certifications	CE, IEC 60601-1-2012	CE, IEC 60601-1-2012

EUROVAC ON TROLLEY