



India's Most Trusted Suction Brand



ELECTRONIC SENSOR



Convenient emptying handles on Lid & Jar
- Controls Infection

JAR



HI VAC PLUS

Main Applications

- Emergency Department
- Intensive Care Unit
- OT / Surgery
- Plastic Surgery
- Obstetrics
- Gastroenterology

TECHNICAL FEATURES

Model	HI VAC PLUS - 90 LPM	HI VAC PLUS - 60 LPM	
Housing	Plastic moulded on two wheels & changeover lever	Plastic moulded on two wheels & changeover lever	Plastic moulded on two wheels & changeover lever
Max. Vacuum / LPM	700 mm Hg, 90 LPM	600 mm Hg, 60 LPM	600 mm Hg, 60 LPM
Pump Type	Double Piston pump	Piston pump	Double Diaphragm pump
Jars	2 x 2.5 Ltrs. PC Jar	2 x 2.5 Ltrs. PC Jar	2 x 4 Ltrs. Polysulfone Jars
Filter	Bacterial Filter Autoclavable / Reusable	Bacterial Filter Autoclavable / Reusable	Bacterial Filter Autoclavable / Reusable
Tubing	10 mm ID x 2 mtr. (PVC)	10 mm ID x 2 mtr. (PVC)	10 mm ID x 2 mtr. (PVC)
Vacuum Gauge	6.25 cm dia 0-760 mm Hg	6.25 cm dia 0-760 mm Hg	6.25 cm dia 0-760 mm Hg
Power Supply	220 V AC, 50 / 60 Hz, 360 W	220 V AC, 50 / 60 Hz, 200 W	220 V AC, 50 / 60 Hz, 180 W
Noise Level	55 dBA ± 3	55 dBA ± 3	55 dBA ± 3
Dimensions	46 x 34 x 86 cms	46 x 34 x 86 cms	46 x 34 x 86 cms
Net Weight	20.5 Kg	17 Kg	22 Kg
Overflow Safety	Mechanical & Electronic Sensor	Mechanical & Electronic Sensor	Mechanical & Electronic Sensor
Optional	4 Ltr. Polysulfone (PSU) Jars 5 Ltr Polycarbonate Jar / 110 V / Foot Switch	4 Ltr. Polysulfone (PSU) Jars 5 Ltr Polycarbonate Jar / 110 V / Foot Switch	110 V / Foot Switch
Certifications	CE, IEC 60601-1-2012	CE, IEC 60601-1-2012	CE, IEC 60601-1-2012

FLOVAC

